

UltraHeat, Inc.

ONE YEAR LIMITED WARRANTY

Warranty #: _____

Expiration Date: _____

- (1) "ONE YEAR LIMITED WARRANTY" from date of purchase and as registered for UltraHeat, Inc. products.
- (2) UltraHeat, Inc. guarantees products to the end user against manufacturing defects from workmanship and material defects.
- (3) Products determined to be defective by UltraHeat, Inc. will be replaced at no charge to the customer.
- (4) UltraHeat, Inc. will NOT PAY for service charges, inspections, or repairs.
- (5) Any modification of UltraHeat products, from original design and use will void the "One Year Limited Warranty".
- (6) Before returning any product for warranty consideration UltraHeat, Inc. must provide a "Return Goods Authorization Number".
- (7) This warranty is void under the following conditions:
 - (a) Improper installation.
 - (b) Not properly following operating instructions when using the heaters (see DVD Owners Manual or visit www.ultraheat.com for operating instructions).
 - (c) Incidental or consequential damage incurred due to improper use for any reason, including accident, abuse, road debris, normal wear and tear, and wear and tear beyond the reasonable limits of the products.

Name: _____

Address: _____

City: _____ **State:** _____ **Zip:** _____

Country: _____

VIN of RV: _____

RV Make: _____ **Model** _____

SAMPLE

OPERATIONAL INSTRUCTIONS

For The Ultra Heat Heaters

Notice...To insure long and satisfying service with the ULTRA HEAT heaters, the following precautions must be taken:

- (1) When the outside temperature starts to approach freezing, turn “ON” the power switch to the ULTRA heaters. The position of the switch will indicate that there is power to the heater circuit.
- (2) There must be liquid in the holding tank, pipes, and elbows when ULTRA HEAT heaters are on.
- (3) When the temperature of the liquid in the holding tank drops to 44° F (6.7° C), the thermostat on the ULTRA HEAT tank heater will automatically turn on. This prevents the liquid in the tank from freezing. When the temperature of the liquid in the holding tank rises to 64° F (18° C), the thermostat on the ULTRA HEAT tank heater turns off. The liquid in the holding tank never gets too warm or too cold.
- (4) Turn the power switch for the tank heaters “OFF” when hooking up to shore power, when starting generator power and when dumping. This precaution will prevent any damage to the thermostat in the ULTRA HEAT tank heater.
- (5) Turn “OFF” power to the ULTRA HEAT heaters when the temperature rises above freezing.
- (6) Check the heater on the exterior holding tanks, pipes and elbows periodically to insure that the ULTRA HEAT heaters are in place. Check the wires and the wire connections to the heaters to insure that they are in place and connected.

**NONCOMPLIANCE WITH THE ABOVE INSTRUCTIONS
VOIDS THE ONE YEAR LIMITED WARRANTY**